



## Q-LINE CL

**LED Indoor surface-mounted ceiling light, 2m, BAP, black, 3000K**

The Q-LINE ceiling light is optionally available with a white, black, or silver-grey luminaire housing. It is also available with a pure white or warm white LED, and different dimensions. Its high luminance and UGR value of less than 10 make the Q-Line luminaire suitable for workstations. Thanks to the TRIAC dimmable LED driver, the luminaire can be directly connected to the 230 Volt mains voltage supply.

## TECHNICAL DATA

|                                     |                        |
|-------------------------------------|------------------------|
| Item no.:                           | 1000692                |
| Lamps included                      | 0                      |
| Number of different light outlets   | 1                      |
| Primary nominal voltage             | 220-240V ~50/60Hz mA/V |
| Secondary power / secondary voltage | 900 mA/V               |
| Length                              | 200.0 cm               |
| Width                               | 6.0 cm                 |
| Height                              | 6.0 cm                 |
| Net weight                          | 4.162 kg               |
| Gross weight                        | 4.96 kg                |
| IP Code                             | IP 20                  |
| Safety class                        | I                      |
| Assembly                            | Surface                |
| Assembly details                    | Ceiling                |
| Wattage                             | 85.0 W                 |
| Lumen                               | 4200 lm                |
| Colour temperature                  | 3000 Kelvin            |
| Beam angle                          | 30 °                   |
| Color                               | black                  |
| CRI                                 | >90                    |
| UGR ?                               | 10.0000                |
| Binning                             | 6                      |



|                |         |
|----------------|---------|
| LXXBXX data    | 70/50   |
| Service life   | 25000 h |
| BIG WHITE Page | 259     |

**Notes**

---

---

---

---

---