



Q-LINE PD

LED indoor pendant, 1m, BAP, white, 3000K

The Q-LINE ceiling light is optionally available with a white, black, or silver-grey luminaire housing. It is also available with a pure white or warm white LED, and different dimensions. Its high luminance and UGR value of less than 10 make the Q-Line luminaire suitable for workstations. Thanks to the TRIAC dimmable LED driver, the luminaire can be directly connected to the 230 Volt mains voltage supply.

TECHNICAL DATA

| | |
|-------------------------------------|------------------------|
| Item no.: | 1000926 |
| Lamps included | 0 |
| Number of different light outlets | 1 |
| Primary nominal voltage | 220-240V ~50/60Hz mA/V |
| Secondary power / secondary voltage | 900 mA/V |
| Length | 100.0 cm |
| Pendant length | 150.0 cm |
| Width | 6.0 cm |
| Height | 6.0 cm |
| Net weight | 2.511 kg |
| Gross weight | 3.034 kg |
| IP Code | IP 20 |
| Safety class | I |
| Assembly | Surface |
| Assembly details | Ceiling |
| Wattage | 45.0 W |
| Lumen | 2100 lm |
| Colour temperature | 3000 Kelvin |
| Beam angle | 30 ° |
| Color | white |
| CRI | >90 |
| UGR ? | 10.0000 |



| | |
|----------------|---------|
| Binning | 6 |
| LXXBXX data | 70/50 |
| Service life | 25000 h |
| BIG WHITE Page | 114 |

Notes
