



## Q-LINE PD

LED Indoor pendant light, 1m, BAP, black, 4000K

The Q-LINE ceiling light is optionally available with a white, black, or silver-grey luminaire housing. It is also available with a pure white or warm white LED, and different dimensions. Its high luminance and UGR value of less than 10 make the Q-Line luminaire suitable for workstations.

Thanks to the TRIAC dimmable LED driver, the luminaire can be directly connected to the 230 Volt mains voltage supply.

## TECHNICAL DATA

Item no.:	1000933
Lamps included	0
Number of different light outlets	1
Primary nominal voltage	220-240V ~50/60Hz mA/V
Secondary power / secondary voltage	900 mA/V
Length	100.0 cm
Pendant length	150.0 cm
Width	6.0 cm
Height	6.0 cm
Net weight	2.505 kg
Gross weight	3.03 kg
IP Code	IP 20
Safety class	I
Assembly	Surface
Assembly details	Ceiling
Wattage	45.0 W
Lumen	2300 lm
Colour temperature	4000 Kelvin
Beam angle	30 °
Color	black
CRI	>90
UGR ?	10.0000

<b>Binning</b>	6
<b>LXXBXX data</b>	70/50
<b>Service life</b>	25000 h
<b>BIG WHITE Page</b>	114

## Notes

---

---

---

---