



KAMUELA

fire protection recessed ceiling light, LED, 4000K, white, 38°, dimmable, IP65

The KAMUEL ECO LED recessed fitting is equipped with an integrated premium LED. The recessed light is made of aluminium and plastic and is fitted with a cold-white LED. The fire-resistant recessed fitting series is fire-resistant for at least 90 minutes. An appropriate dimmable constant current driver is integrated for operating the recessed fitting, and is therefore suitable for direct connection to 230 Volts. This luminaire contains built-in LED lamps and is available with different housing colours.

TECHNICAL DATA

| | |
|-------------------------|---------------------------|
| Item no.: | 1001018 |
| Lamps included | 0 |
| Primary nominal voltage | 220-240V ~50Hz mA/V |
| Height | 7.1 cm |
| Diameter | 8.8 cm |
| Installation diameter | 7.0 cm |
| Installation depth | 7.1 cm |
| Net weight | 0.267 kg |
| Gross weight | 0.326 kg |
| IP Code | IP 65 |
| Safety class | II |
| Impact resistance class | IK02 |
| Impact resistance | 0,20000000000000001 Joule |
| Assembly | Recessed |
| Assembly details | Ceiling |
| Wattage | 6.5 W |
| Lumen | 400 lm |
| Colour temperature | 4000 Kelvin |
| Beam angle | 38 ° |
| Color | white |
| CRI | >80 |
| Binning | 6 |



| | |
|----------------|---------|
| LXXBXX data | 70/50 |
| Service life | 25000 h |
| BIG WHITE Page | 463 |

Notes
