




DOLIX OUT QR-C51

square, white

The DOLIX OUT low-voltage recessed ceiling light is made from aluminium and is equipped with a glass for protection against splashing water. Rated IP65 it can be used outdoors or in damp areas. To operate the recessed fitting, a matching transformer for low-voltage halogen lamps is required.



TECHNICAL DATA

| | |
|-------------------------|---------------------------|
| Item no.: | 1001161 |
| Socket | GX5.3 |
| Lamp | QR-C51 |
| Number of sockets | 1 |
| Lamps included | 0 |
| Primary nominal voltage | 12V ~50Hz mA/V |
| Length | 8.8 cm |
| Width | 8.8 cm |
| Height | 11.0 cm |
| Installation diameter | 6.8 cm |
| Installation depth | 11.0 cm |
| Net weight | 0.182 kg |
| Gross weight | 0.212 kg |
| IP Code | IP 65 |
| Safety class | III |
| Impact resistance class | IK02 |
| Impact resistance | 0,20000000000000001 Joule |
| Assembly | Recessed |
| Assembly details | Ceiling |
| Wattage | 50.0 W |
| Color | white |
| BIG WHITE Page | 460 |

Recommended lamp

| | |
|---------|--|
| 1001574 | Philips Master LED Spot MR16 , 5W, 2700K, 36°, dimmable |
| 1001575 | Philips Master LED MR16 5W , 3000K, 36° |
| 551862 | LED QR-C51 , lamp, 5W, COB LED, 38°, 2700K, not dimmable |

Notes
