


DOLIX OUT

Outdoor recessed fitting, QR-C51, IP65, square, silver-grey, max. 35W, incl. clip springs

The DOLIX OUT low-voltage recessed ceiling light is made from aluminium and is equipped with a glass for protection against splashing water. Rated IP65 it can be used outdoors or in damp areas. To operate the recessed fitting, a matching transformer for low-voltage halogen lamps is required.



TECHNICAL DATA

Item no.:	1001164		
Socket	GX5.3		
Lamp	QR-C51		
Number of sockets	1		
Lamps included	0		
Primary nominal voltage	12V ~50Hz mA/V		
Length	8.8 cm		
Width	8.8 cm		
Height	11.0 cm		
Installation diameter	6.8 cm		
Installation depth	11.0 cm		
Net weight	0.179 kg		
Gross weight	0.212 kg		
IP Code	IP 65		
Safety class	III		
Impact resistance class	IK02		
Impact resistance	0,2000000000000001 Joule		
Assembly	Recessed		
Assembly details	Ceiling		
Wattage	50.0 W		
Color	grey		
<u> </u>	<u> </u>		





Recommended lamp

1001574	Philips Master LED Spot MR16 , 5W, 2700K, 36°, dimmable
1001575	Philips Master LED MR16 5W , 3000K, 36°
551862	LED QR-C51 , lamp, 5W, COB LED, 38°, 2700K, not dimmable

Notes			