




LED PANEL ROUND

pendant, white, 360LED, 40W, dimmable 1-10V, 3000K

The LED PANEL pendant is available in three different light colours and impresses with its ultra-flat shape and its powerful, dimmable LED modules. The aluminium frame is fitted with an acrylic glass cover which ensures homogeneous and glare-free illumination. The built-in LED driver allows direct connection to a mains supply of 100V to 240V.

TECHNICAL DATA

| Item no.: | 1001344 | | |
|-------------------------------------|------------------------|--|--|
| Primary nominal voltage | 100-240V ~50/60Hz mA/V | | |
| Secondary power / secondary voltage | 1000 mA/V | | |
| Pendant length | 200.0 cm | | |
| Height | 3.2 cm | | |
| Diameter | 60.0 cm | | |
| Net weight | 4.405 kg | | |
| Gross weight | 5.738 kg | | |
| IP Code | IP 20 | | |
| Safety class | I | | |
| Assembly | Surface | | |
| Assembly details | Ceiling | | |
| Wattage | 42.0 W | | |
| Lumen | 3150 lm | | |
| Colour temperature | 3000 Kelvin | | |
| Beam angle | 110° | | |
| Color | white | | |
| CRI | >80 | | |
| UGR ? | 22.0000 | | |
| Binning | 6 | | |
| LXXBXX data | 70/50 | | |
| Service life | 30000 h | | |
| | | | |





| BIG WHITE Page | 104 |
|----------------|-----|

Accessories

| 470505 EP1 DIMMER , 1-10V, max. 10W | |
|-------------------------------------|--|
|-------------------------------------|--|

| Notes | | | |
|-------|--|--|--|
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |