



## TEC KALU double

black, 60°, 3000K, incl. 3-circuit adapter

The futuristic 240V TEC KALU with an appropriate adapter for the 3-circuit 240V track system has individually rotating and swivelling lamp heads with warm-white and dimmable premium LEDs. The built-in LED driver is located within the main structure. TEC KALU is supplied ready for direct connection to the 230V mains voltage supply.

### TECHNICAL DATA

Item no.:	1001419
Primary nominal voltage	220-240V ~50/60Hz mA/V
Secondary power / secondary voltage	700 mA/V
Vertical tilting range	120 °
Horizontal rotation range	360 °
Length	29.5 cm
Width	17.0 cm
Height	15.5 cm
Net weight	1.671 kg
Gross weight	2.136 kg
IP Code	IP 20
Safety class	I
Assembly	Surface
Assembly details	Track Ceiling
Dimmable	Ja
Dimming technology	trailing edge
Wattage	31.0 W
Lumen	1900 lm
Colour temperature	3000 Kelvin
Beam angle	60 °
Color	black
CRI	>80



Binning	6
LXXBXX data	70/50
Service life	40000 h
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
BIG WHITE Page	352

### Notes

---

---

---

---

---