



TEC KALU quad

black, 24°, 3000K, incl. 3-circuit adapter

The futuristic 240V TEC KALU with an appropriate adapter for the 3-circuit 240V track system has individually rotating and swivelling lamp heads with warm-white and dimmable premium LEDs. The built-in LED driver is located within the main structure. TEC KALU is supplied ready for direct connection to the 230V mains voltage supply.

TECHNICAL DATA

| | |
|-------------------------------------|------------------------|
| Item no.: | 1001429 |
| Primary nominal voltage | 220-240V ~50/60Hz mA/V |
| Secondary power / secondary voltage | 700 mA/V |
| Vertical tilting range | 120 ° |
| Horizontal rotation range | 360 ° |
| Length | 29.5 cm |
| Width | 24.5 cm |
| Height | 15.5 cm |
| Net weight | 2.573 kg |
| Gross weight | 3.332 kg |
| IP Code | IP 20 |
| Safety class | I |
| Assembly | Surface |
| Assembly details | Track Ceiling |
| Dimmable | Ja |
| Dimming technology | trailing edge |
| Wattage | 60.0 W |
| Lumen | 3800 lm |
| Colour temperature | 3000 Kelvin |
| Beam angle | 24 ° |
| Color | black |
| CRI | >80 |



| | |
|-----------------------------|---------|
| Binning | 6 |
| LXXBXX data | 70/50 |
| Service life | 40000 h |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 40 °C |
| BIG WHITE Page | 352 |

Notes
