



TEC KALU CW

LED Indoor surface-mounted wall and ceiling light, double, black, 24°, 3000K

This futuristic 240V wall and ceiling light TEC KALU has individually rotating and swivelling lamp heads, equipped with warm white and dimmable Premium LEDs. The built-in LED driver is located within the main structure. An optionally available suspension allows pendulum mode. TEC KALU is supplied ready for direct connection to the 230V mains voltage supply.

TECHNICAL DATA

| | |
|-------------------------------------|------------------------|
| Item no.: | 1001431 |
| Primary nominal voltage | 220-240V ~50/60Hz mA/V |
| Secondary power / secondary voltage | 700 mA/V |
| Vertical tilting range | 120 ° |
| Horizontal rotation range | 360 ° |
| Length | 29.5 cm |
| Width | 17.0 cm |
| Height | 15.3 cm |
| Net weight | 1.8 kg |
| Gross weight | 1.926 kg |
| IP Code | IP 20 |
| Safety class | I |
| Assembly | Surface |
| Assembly details | Ceiling |
| Dimmable | Ja |
| Dimming technology | trailing edge |
| Wattage | 31.0 W |
| Lumen | 1900 lm |
| Colour temperature | 3000 Kelvin |
| Beam angle | 24 ° |
| Color | black |
| CRI | >80 |

Accessories

| | |
|---------|---------------------------------|
| 1001435 | TEC KALU suspension set , black |
| 1001436 | TEC KALU suspension set , white |

| | |
|-----------------------------|---------|
| Binning | 6 |
| LXXBXX data | 70/50 |
| Service life | 40000 h |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 40 °C |
| BIG WHITE Page | 268 |

Notes
