



## TEC KALU CW

**LED Indoor surface-mounted wall and ceiling light double, white/black 24° 3000K**

This futuristic 240V wall and ceiling light TEC KALU has individually rotating and swivelling lamp heads, equipped with warm white and dimmable Premium LEDs. The built-in LED driver is located within the main structure. An optionally available suspension allows pendulum mode. TEC KALU is supplied ready for direct connection to the 230V mains voltage supply.

### TECHNICAL DATA

Item no.:	1001432
Primary nominal voltage	220-240V ~50/60Hz mA/V
Secondary power / secondary voltage	700 mA/V
Vertical tilting range	120 °
Horizontal rotation range	360 °
Length	29.5 cm
Width	17.0 cm
Height	15.3 cm
Net weight	1.8 kg
Gross weight	1.926 kg
IP Code	IP 20
Safety class	I
Assembly	Surface
Assembly details	Ceiling
Dimmable	Ja
Dimming technology	trailing edge
Wattage	31.0 W
Lumen	1900 lm
Colour temperature	3000 Kelvin
Beam angle	24 °
Color	white
CRI	>80

## Accessories

1001435	TEC KALU suspension set , black
1001436	TEC KALU suspension set , white

Binning	6
LXXBXX data	70/50
Service life	40000 h
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
BIG WHITE Page	268

## Notes

---

---

---

---

---