## а. л . . . . . . . . . . . . . Л ы . . . . . . . . . . . а а а ..... ы л . . . . . . . . . . . . . ы 111 ..... л






## LED OUTDOOR BEAM

## warm white, 10W, 3000K, 100°, IP65

Powerful OUTDOOR BEAM spot for illuminating areas and spaces. With a tiltable installation bracket and protection class IP65, the spot is suitable for outdoor installation on the wall, ceiling or on the floor. The electrical connection of the spot, which is available in warm white and neutral white, is made directly by the built-in driver and the connection lead with mains plug to the 230V mains supply. An earth spike is available as an option for simplified floor installation.



## **TECHNICAL DATA**

Item no.:	1001634	
Lamps included	0	
Primary nominal voltage	220-240V ~50/60Hz mA/V	
Secondary power / secondary voltage	120 mA/V	
Vertical tilting range	90 °	
Length	11.3 cm	
Width	8.5 cm	
Height	13.0 cm	
Net weight	0.754 kg	
Gross weight	0.833 kg	
IP Code	IP 65	
Safety class	1	
Impact resistance class	IK04	
Impact resistance	0,5 Joule	
Assembly	Surface	
Assembly details	Ceiling,Ground,Wall	
Wattage	e 11.0 W	
Lumen	725 lm	
Colour temperature	3000 Kelvin	
Beam angle	100 °	
Color	grey	
CRI	>80	



		Binning	3
Accessories		LXXBXX data	70/50
		Service life	30000 h
234344 WALL MOUNTING BRACKET , for OUTDOOR BEAM and MILOX, silver, 50 cm	Maximum ambient temperature	40 °C	
		BIG WHITE Page	604
234354	WALL MOUNTING BRACKET , for OUTDOOR BEAM and MILOX, silver, 80 cm		
900011	PLASTIC EARTH SPIKE , black, length 17.5cm		

Notes