



## NOBLO SPOT

black, 2700K, 36°, incl. 1-circuit adapter

Adjustable LED spot NOBLO with suitable adapter for the 240V 1-circuit track system. The luminaire impresses with its slim design and is therefore ideal for modern lighting concepts. The luminaire is made from aluminium and equipped with a Premium LED module.

### TECHNICAL DATA

|                                     |                           |
|-------------------------------------|---------------------------|
| Item no.:                           | 1001862                   |
| Primary nominal voltage             | 220-240V ~50/60Hz mA/V    |
| Secondary power / secondary voltage | 350 mA/V                  |
| Vertical tilting range              | 90 °                      |
| Horizontal rotation range           | 320 °                     |
| Length                              | 10.5 cm                   |
| Height                              | 10.7 cm                   |
| Diameter                            | 5.0 cm                    |
| Net weight                          | 0.223 kg                  |
| Gross weight                        | 0.306 kg                  |
| IP Code                             | IP 20                     |
| Safety class                        | II                        |
| Assembly                            | Surface                   |
| Assembly details                    | Track Ceiling, Track Wall |
| Wattage                             | 7.5 W                     |
| Lumen                               | 620 lm                    |
| Colour temperature                  | 2700 Kelvin               |
| Beam angle                          | 36 °                      |
| Color                               | black                     |
| CRI                                 | >80                       |
| Binning                             | 6                         |
| LXXBXX data                         | 70/50                     |



|                             |         |
|-----------------------------|---------|
| Service life                | 30000 h |
| Maximum ambient temperature | 40 °C   |
| BIG WHITE Page              | 396     |

**Notes**

---

---

---

---

---