



AROSA

1,25m, TRIAC, PD, LED indoor pendant, black, 3000K

The AROSA pendant, available in two lengths, is equipped with white, black or anodised aluminium housing as desired. A PMMA diffuser, which is used on the upper and lower light outlet, provides glare-free lighting characteristics. The integrated warm-white LEDs provide a high degree of light output. Thanks to the TRIAC dimmable LED driver, the luminaire can be directly connected to the 230 Volt mains voltage supply.

TECHNICAL DATA

| | |
|-------------------------------------|------------------------|
| Item no.: | 1001940 |
| Number of different light outlets | 2 |
| Primary nominal voltage | 220-240V ~50/60Hz mA/V |
| Secondary power / secondary voltage | 500 mA/V |
| Length | 125.3 cm |
| Pendant length | 200.0 cm |
| Width | 2.7 cm |
| Height | 4.2 cm |
| Net weight | 2.299 kg |
| Gross weight | 2.986 kg |
| IP Code | IP 20 |
| Safety class | I |
| Assembly | Surface |
| Assembly details | Ceiling |
| Dimmable | Ja |
| Dimming technology | trailing edge |
| Wattage | 32.0 W |
| Lumen | 1700 lm |
| Colour temperature | 3000 Kelvin |
| Beam angle | 110 ° |
| Color | black |
| CRI | >80 |



| | |
|-----------------------------|---------|
| Binning | 3 |
| Binning 2 | 3 |
| LXXBXX data | 70/50 |
| Service life | 40000 h |
| Service life 2 | 40000 h |
| Ambient temperature | 25 °C |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 35 °C |
| BIG WHITE Page | 53 |

Notes
