



MECANICA PLUS TL

indoor LED table lamp, 2700-6500K, black

High quality LED table lamp MECANICA PLUS. An extremely minimalist design combined with three joints and the possibility of infinitely variable light colour selection make this luminaire the perfect desk lamp. By the potentially large reach and a stable base the light reaches even the most distant corners of the table. The integrated switch switch facilitates the operation of the luminaire. The electrical connection is made directly to the 230V mains supply. This luminaire contains built-in LED lamps.

TECHNICAL DATA

Primary nominal voltage 100-240V ~50/60Hz mA/V Secondary power / secondary voltage 12 mA/V Vertical tilting range 306 ° Horizontal rotation range 329 ° Height 51.1 cm Net weight 4.26 kg IP Code IP 20 Safety class II Assembly Mobile Wattage 7.0 W Lumen 450 Im Beam angle 100 ° Color black CRI >80 Binning 6 LXXBXX data 70/50 Service life 30000 h BIG WHITE Page 27	Item no.:	1002404
Vertical tilting range 306 ° Horizontal rotation range 329 ° Height 51.1 cm Net weight 3.2 kg Gross weight 4.26 kg IP Code IP 20 Safety class II Assembly Mobile Wattage 7.0 W Lumen 450 lm Beam angle 100 ° Color black CRI >80 Binning 6 LXXBXX data 70/50 Service life 30000 h	Primary nominal voltage	100-240V ~50/60Hz mA/V
Height 51.1 cm Net weight 3.2 kg Gross weight 4.26 kg IP Code IP 20 Safety class II Assembly Mobile Wattage 7.0 W Lumen 450 lm Beam angle 100 ° Color black CRI >80 Binning 6 LXXBXX data 70/50 Service life 30000 h	Secondary power / secondary voltage	12 mA/V
Height 51.1 cm Net weight 3.2 kg Gross weight 4.26 kg IP Code IP 20 Safety class II Assembly Mobile Wattage 7.0 W Lumen 450 lm Beam angle 100 ° Color black CRI >80 Binning 6 LXXBXX data 70/50 Service life 30000 h	Vertical tilting range	306°
Net weight 3.2 kg Gross weight 4.26 kg IP Code IP 20 Safety class II Assembly Mobile Wattage 7.0 W Lumen 450 lm Beam angle 100 ° Color black CRI >80 Binning 6 LXXBXX data 70/50 Service life 30000 h	Horizontal rotation range	329 °
Gross weight 4.26 kg IP Code IP 20 Safety class II Assembly Mobile Wattage 7.0 W Lumen 450 lm Beam angle 100 ° Color black CRI >80 Binning 6 LXXBXX data 70/50 Service life 30000 h	Height	51.1 cm
IP Code	Net weight	3.2 kg
Safety class II Assembly Mobile Wattage 7.0 W Lumen 450 lm Beam angle 100 ° Color black CRI >80 Binning 6 LXXBXX data 70/50 Service life 30000 h	Gross weight	4.26 kg
Assembly Mobile Wattage 7.0 W Lumen 450 lm Beam angle 100 ° Color black CRI >80 Binning 6 LXXBXX data 70/50 Service life 30000 h	IP Code	IP 20
Wattage 7.0 W Lumen 450 lm Beam angle 100 ° Color black CRI >80 Binning 6 LXXBXX data 70/50 Service life 30000 h	Safety class	II
Lumen 450 lm Beam angle 100 ° Color black CRI >80 Binning 6 LXXBXX data 70/50 Service life 30000 h	Assembly	Mobile
Beam angle	Wattage	7.0 W
Color black CRI >80 Binning 6 LXXBXX data 70/50 Service life 30000 h	Lumen	450 lm
CRI >80 Binning 6 LXXBXX data 70/50 Service life 30000 h	Beam angle	100 °
Binning 6 LXXBXX data 70/50 Service life 30000 h	Color	black
LXXBXX data 70/50 Service life 30000 h	CRI	>80
Service life 30000 h	Binning	6
	LXXBXX data	70/50
BIG WHITE Page 27	Service life	30000 h
	BIG WHITE Page	27

							4				4			4		ч		ч	ч	ч	ч	ч	J	4	4	4	4								
	4	- 4		ı	a,	J,	J.	J	4	a	J	J	J	J	ä	a	ä	ä	J.																
١.	ı .	LL	1	1	ı	ı	J	J.	J	4	J	J	J	J	J	J	J		1			ı		1		1	ı	1	ı	J.	a,	١,	1	1	1
					ı			á		ā		J	ä	J	ä	ä	J	J	J.	J	J.	J.	J.	. د	1	J	J.	ă,							



Notes			