





MECANICA PLUS FL

indoor LED floor stand, 2700-6500K, black

High quality LED floor stand MECANICA PLUS. An extremely minimalist design combined with three joints and the possibility of infinitely variable light colour selection make this luminaire the perfect floor stand. By the potentially large reach and a stable base the light reaches even the most distant corners of the table. The integrated switch switch facilitates the operation of the luminaire. The electrical connection is made directly to the 230V mains supply. This luminaire contains built-in LED lamps.

TECHNICAL DATA

Primary nominal voltage100-240V ~50/60Hz mAVVSecondary power / secondary voltage12 mAVVVertical tilting range306 °Horizontal rotation range329 °Height136.0 cmNet weight5.76 kgGross weight7.86 kgIP CodeIP 20Safety classIIAssemblyMobileWattage7.0 WLumen450 lmBeam angle100 °ColorblackCRI>80Binning6LXXBXX data70/50	Item no.:	1002405
Vertical tilting range306 °Horizontal rotation range329 °Height136.0 cmNet weight5.76 kgGross weight7.86 kgIP CodeIP 20Safety classIIAssemblyMobileWattage7.0 WLumen450 lmBeam angle100 °ColorblackCRI>80Binning6	Primary nominal voltage	100-240V ~50/60Hz mA/V
Horizontal rotation range 329 ° Height 136.0 cm Net weight 5.76 kg Gross weight 7.86 kg IP Code IP 20 Safety class II Assembly Mobile Wattage 7.0 W Lumen 450 lm Beam angle 100 ° Color black CRI >80 Binning 6	Secondary power / secondary voltage	12 mA/V
Height 136.0 cm Net weight 5.76 kg Gross weight 7.86 kg IP Code IP 20 Safety class II Assembly Mobile Wattage 7.0 W Lumen 450 lm Beam angle 100 ° Color black CRI >80 Binning 6	Vertical tilting range	306°
Net weight 5.76 kg Gross weight 7.86 kg IP Code IP 20 Safety class II Assembly Mobile Wattage 7.0 W Lumen 450 lm Beam angle 100 ° Color black CRI >80 Binning 6	Horizontal rotation range	329 °
Gross weight 7.86 kg IP Code IP 20 Safety class II Assembly Mobile Wattage 7.0 W Lumen 450 lm Beam angle 100 ° Color black CRI >80 Binning 6	Height	136.0 cm
IP Code IP 20 Safety class II Assembly Mobile Wattage 7.0 W Lumen 450 lm Beam angle 100 ° Color black CRI >80 Binning 6	Net weight	5.76 kg
Safety class II Assembly Mobile Wattage 7.0 W Lumen 450 lm Beam angle 100 ° Color black CRI >80 Binning 6	Gross weight	7.86 kg
Assembly Mobile Wattage 7.0 W Lumen 450 lm Beam angle 100 ° Color black CRI >80 Binning 6	IP Code	IP 20
Wattage 7.0 W Lumen 450 lm Beam angle 100 ° Color black CRI >80 Binning 6	Safety class	II
Lumen 450 lm Beam angle 100 ° Color black CRI >80 Binning 6	Assembly	Mobile
Beam angle 100 ° Color black CRI >80 Binning 6	Wattage	7.0 W
Color black CRI >80 Binning 6	Lumen	450 lm
CRI >80 Binning 6	Beam angle	100 °
Binning 6	Color	black
	CRI	>80
LXXBXX data 70/50	Binning	6
	LXXBXX data	70/50
Service life 30000 h	Service life	30000 h
BIG WHITE Page 27	BIG WHITE Page	27

							4				4			4		ч		ч	ч	ч	ч	ч	J	4	4	4	4								
	4	- 4		ı	a,	J,	J.	J	4	a	J	J	J	J	ä	a	ä	ä	J.																
١.	ı .	LL	1	1	ı	ı	J	J.	4	4	J	J	J	J	J	J	J		4			ı		1		1	ı	1	ı	J.	a,	١,	1	1	1
					ı			á		ā		J	ä	J	ä	ä	J	J	J.	J	J.	J.	J.	. د	1	J	J.	ă,							



Notes			