




EURO SPOT TRACK DALI black

4000K, 15°, incl. 3-circuit adapter

Rotating and swivelling EURO SPOT TRACK DALI 240V LED spotlight, with a compact design with suitable adapter for the 3-circuit 240V track system. The LED light source is installed in the cylindrical lamp head in the factory. The spotlight, which is available with several housing colours and beam angles, is captivating because of its high light output, DALI compatibility and its simple and timeless appearance.



TECHNICAL DATA

| Item no.: | 1002811 |
|-------------------------------------|------------------------|
| Primary nominal voltage | 220-240V ~50/60Hz mA/V |
| Secondary power / secondary voltage | 1000 mA/V |
| Vertical tilting range | 90 ° |
| Horizontal rotation range | 350 ° |
| Length | 23.5 cm |
| Height | 22.5 cm |
| Diameter | 12.5 cm |
| Net weight | 2.073 kg |
| Gross weight | 2.53 kg |
| IP Code | IP 20 |
| Safety class | I |
| Assembly details | Track Ceiling |
| Dimmable | Ja |
| Dimming technology | DALI |
| Wattage | 42.0 W |
| Lumen | 3200 lm |
| Colour temperature | 4000 Kelvin |
| Beam angle | 15 ° |
| Color | black |
| Binning | 3 |
| LXXBXX data | 70/50 |
| | |





| Service life | 30000 h |
|---------------------|---------|
| Ambient temperature | 25 °C |
| BIG WHITE Page | 334 |

| Notes | |
|-------|--|
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |