




RETRATO

Indoor LED surface-mounted wall light, 3000K, white

RETRATO WL in which the canopy and the lamp head are connected via an arm together with two joint pieces. The incorporated LEDs make it possible to provide your exhibits with gentle illumination by UV-free LED light without significant heat dissipation. Both assembled joints ensure that the lamp is aligned perfectly. The luminaire is available in several housing colours. Thanks to the assembled LED power supply, the electrical connection of the luminaire is made directly via 230V mains power supply. This luminaire contains built-in LED lamps.



TECHNICAL DATA

| Item no.: | 1002960 |
|-------------------------------------|------------------------|
| Primary nominal voltage | 220-240V ~50/60Hz mA/V |
| Secondary power / secondary voltage | 500 mA/V |
| Vertical tilting range | 90 ° |
| Horizontal rotation range | 330 ° |
| Length | 30.0 cm |
| Width | 5.2 cm |
| Height | 20.1 cm |
| Net weight | 0.538 kg |
| Gross weight | 0.89 kg |
| IP Code | IP 20 |
| Safety class | I |
| Assembly | Surface |
| Assembly details | Wall |
| Wattage | 12.0 W |
| Lumen | 730 lm |
| Colour temperature | 3000 Kelvin |
| Beam angle | 100° |
| Color | white |
| CRI | >90 |
| Binning | 3 |
| LXXBXX data | 70/50 |
| | |





| Service life | 30000 h |
|-----------------------------|---------|
| Maximum ambient temperature | 35 °C |
| BIG WHITE Page | 223 |

| Notes | |
|-------|--|
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |