




RETRATO

Indoor LED surface-mounted wall light, 3000K, chrome

RETRATO WL in which the canopy and the lamp head are connected via an arm together with two joint pieces. The incorporated LEDs make it possible to provide your exhibits with gentle illumination by UV-free LED light without significant heat dissipation. Both assembled joints ensure that the lamp is aligned perfectly. The luminaire is available in several housing colours. Thanks to the assembled LED power supply, the electrical connection of the luminaire is made directly via 230V mains power supply. This luminaire contains built-in LED lamps.



TECHNICAL DATA

Item no.:	1002961
Primary nominal voltage	220-240V ~50/60Hz mA/V
Secondary power / secondary voltage	500 mA/V
Vertical tilting range	90 °
Horizontal rotation range	330 °
Length	30.0 cm
Width	5.2 cm
Height	20.1 cm
Net weight	0.541 kg
Gross weight	0.896 kg
IP Code	IP 20
Safety class	I
Assembly	Surface
Assembly details	Wall
Wattage	12.0 W
Lumen	730 lm
Colour temperature	3000 Kelvin
Beam angle	100 °
Color	chrome
CRI	>90
Binning	6
LXXBXX data	70/50



Service life	30000 h
Maximum ambient temperature	35 °C
BIG WHITE Page	223

Notes
