


NOBLO II

Indoor LED surface-mounted ceiling light 2700K black

NOBLO rotating and tilting LED spotlight for surface mounting on walls and ceilings. The luminaire impresses with its slim design and is therefore ideal for modern lighting concepts. The luminaire is made from aluminium and equipped with a Premium LED module. The luminaire is available in three housing colours with two or three light outlets.



TECHNICAL DATA

| Item no.: | 1002973 | | | |
|-------------------------------------|------------------------|--|--|--|
| Primary nominal voltage | 220-240V ~50/60Hz mA/V | | | |
| Secondary power / secondary voltage | 350 mA/V | | | |
| Vertical tilting range | 90 ° | | | |
| Horizontal rotation range | 350 ° | | | |
| Length | 24.0 cm | | | |
| Width | 10.5 cm | | | |
| Height | 12.7 cm | | | |
| Net weight | 0.668 kg | | | |
| Gross weight | 0.905 kg | | | |
| IP Code | IP 20 | | | |
| Safety class | I | | | |
| Assembly | Surface | | | |
| Assembly details | Ceiling,Wall | | | |
| Wattage | 16.0 W | | | |
| Lumen | 1200 lm | | | |
| Colour temperature | 2700 Kelvin | | | |
| Beam angle | 36 ° | | | |
| Color | black | | | |
| CRI | >80 | | | |
| Binning | 6 | | | |
| LXXBXX data | 70/50 | | | |
| | • | | | |





| Service life | 30000 h |
|----------------|---------|
| BIG WHITE Page | 297 |

| Notes | | | |
|-------|--|--|--|
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |