



## SENSER 12

Indoor LED recessed ceiling light square white 3000K

The SENSER recessed fitting made from aluminium is available in white and silver-grey, and with a round or square shade. The rigid Premium LED insert produces homogeneous base illumination over a wide area thanks to its extensive beam angle. If you are looking for a recessed ceiling light with a shallow installation depth, SENSER is just the job.

## **TECHNICAL DATA**

| Item no.:                           | 1003011                  |  |  |
|-------------------------------------|--------------------------|--|--|
| Secondary power / secondary voltage | 200 mA/V                 |  |  |
| Length                              | 11.5 cm                  |  |  |
| Width                               | 11.5 cm                  |  |  |
| Height                              | 2.0 cm                   |  |  |
| Installation length                 | 10.5 cm                  |  |  |
| Installation width                  | 10.5 cm                  |  |  |
| Installation depth                  | 3.0 cm                   |  |  |
| Net weight                          | 0.131 kg                 |  |  |
| Gross weight                        | 0.171 kg                 |  |  |
| IP Code                             | IP 20                    |  |  |
| Safety class                        | III                      |  |  |
| Impact resistance class             | IK02                     |  |  |
| Impact resistance                   | 0,2000000000000001 Joule |  |  |
| Assembly                            | Recessed                 |  |  |
| Assembly details                    | Ceiling                  |  |  |
| Wattage                             | 6.0 W                    |  |  |
| Lumen                               | 440 lm                   |  |  |
| Colour temperature                  | 3000 Kelvin              |  |  |
| Color                               | white                    |  |  |
| CRI                                 | >80                      |  |  |
| Binning                             | 6                        |  |  |
|                                     |                          |  |  |



## Accessories

| 1003254 LED driver , 5 - 8.4W 200mA |
|-------------------------------------|
|                                     |

| LXXBXX data         | 70/50   |
|---------------------|---------|
| Service life        | 48000 h |
| Ambient temperature | 25 °C   |
| BIG WHITE Page      | 511     |

| Notes |  |  |  |
|-------|--|--|--|
|       |  |  |  |
|       |  |  |  |
|       |  |  |  |
|       |  |  |  |
|       |  |  |  |
|       |  |  |  |
|       |  |  |  |
|       |  |  |  |
|       |  |  |  |