а – J. - a ы . **...** ы н ы л ы J л ы гг ГГ ы Л J.






DOLIX OUT

Outdoor recessed fitting, QR-C51, IP65, square, silver-grey, max. 35W, incl. clip springs

The DOLIX OUT low-voltage recessed ceiling light is made from aluminium and is equipped with a glass for protection against splashing water. Rated IP65 it can be used outdoors or in damp areas. To operate the recessed fitting, a matching transformer for low-voltage halogen lamps is required.



TECHNICAL DATA

| Item no.: | 111128 |
|-------------------------|----------------|
| Socket | GX5.3 |
| Lamp | QR-C51 |
| Number of sockets | 1 |
| Lamps included | 0 |
| Primary nominal voltage | 12V ~50Hz mA/V |
| Length | 8.9 cm |
| Width | 8.9 cm |
| Height | 14.0 cm |
| Installation diameter | 7.0 cm |
| Installation depth | 13.5 cm |
| Net weight | 0.331 kg |
| Gross weight | 0.37 kg |
| IP Code | IP 65 |
| Safety class | 111 |
| Assembly | Recessed |
| Assembly details | Ceiling |
| Wattage | 35.0 W |
| Color | grey |
| | |

Recommended lamp

| 1001574 | Philips Master LED Spot MR16 , 5W, 2700K, 36°, dimmable |
|---------|--|
| 1001575 | Philips Master LED MR16 5W , 3000K, 36° |
| 551862 | LED QR-C51 , lamp, 5W, COB LED, 38°, 2700K, not dimmable |

Accessories

227160 TRANSFORMER , 60VA, 12V, IP44

Notes