



## PIKA

recessed fitting, QR-C51, round, white, tiltable, max. 50W, incl. clip springs

The adjustable low-voltage recessed fitting PIKA is available in white, chrome, brass and silver-grey colour and allows independent adjustment of the desired beam angle. To operate the recessed fitting, a matching transformer with 12V alternating current is required.

## TECHNICAL DATA

|                         |                   |
|-------------------------|-------------------|
| Item no.:               | 111171            |
| Socket                  | G5.3              |
| Lamp                    | QR-C51            |
| Number of sockets       | 1                 |
| Lamps included          | 0                 |
| Primary nominal voltage | 12V ~50/60Hz mA/V |
| Tilt range              | 45 °              |
| Height                  | 9.0 cm            |
| Diameter                | 8.3 cm            |
| Installation diameter   | 7.5 cm            |
| Installation depth      | 9.5 cm            |
| Net weight              | 0.117 kg          |
| Gross weight            | 0.142 kg          |
| IP Code                 | IP 20             |
| Safety class            | III               |
| Assembly                | Recessed          |
| Assembly details        | Ceiling           |
| Wattage                 | 50.0 W            |
| Color                   | white             |

## Recommended lamp

|         |   |
|---------|---|
| 1001574 | Philips Master LED Spot MR16 , 5W, 2700K, 36°, dimmable |
| 1001575 | Philips Master LED MR16 5W , 3000K, 36°                 |

## Accessories

|        |   |
|--------|---|
| 461067 | ELECTRONIC TRANSFORMER 01 , 60VA, 12V FN I, 12V, 60VA |
|--------|---|

## Notes

---

---

---

---

---