



PIKA

recessed fitting, QR-C51, round, silver-grey, rigid, max. 50W, incl. clip springs

The rigid low-voltage recessed fitting PIKA is available in white, chrome, brass and silver-grey colour and is equipped with an MR16 socket for low-voltage halogen lamps. To operate the recessed fitting, a matching transformer with 12V alternating current is required.

TECHNICAL DATA

| | |
|-------------------------|-------------------|
| Item no.: | 111189 |
| Socket | G5.3 |
| Lamp | QR-C51 |
| Number of sockets | 1 |
| Lamps included | 0 |
| Primary nominal voltage | 12V ~50/60Hz mA/V |
| Height | 9.0 cm |
| Diameter | 7.8 cm |
| Installation diameter | 6.0 cm |
| Installation depth | 9.5 cm |
| Net weight | 0.083 kg |
| Gross weight | 0.108 kg |
| IP Code | IP 20 |
| Safety class | III |
| Assembly | Recessed |
| Assembly details | Ceiling |
| Wattage | 50.0 W |
| Color | grey |

Recommended lamp

| | |
|---------|---|
| 1001574 | Philips Master LED Spot MR16 , 5W, 2700K, 36°, dimmable |
| 1001575 | Philips Master LED MR16 5W , 3000K, 36° |

Accessories

| | |
|--------|---|
| 461067 | ELECTRONIC TRANSFORMER 01 , 60VA, 12V FN I, 12V, 60VA |
|--------|---|

Notes
