

QUADRASYL 44 WITH BRACKET

outdoor spot, IP44, square, silver-grey, GX53, max. 9W

The high-voltage recessed fitting QUADRASYL 44 WITH BRACKET is made from aluminium and is designed for the use of energy-saving GX53 lamps. A front cover made from stainless steel 316 completes the puristic and linear design. Rated IP44 QUADRASYL can be used in outdoor applications as well as damp areas. The incorporated bracket guarantees the individual adjustment of the fitting.

TECHNICAL DATA

| Item no.: | 111522 |
|-------------------------|---------------------|
| Socket | GX53 |
| Lamp | TCR-TSE |
| Number of sockets | 1 |
| Lamps included | 0 |
| Primary nominal voltage | 230V ~50Hz mA/V |
| Tilt range | 350 ° |
| Width | 13.5 cm |
| Height | 13.5 cm |
| Depth | 11.0 cm |
| Net weight | 0.865 kg |
| Gross weight | 1.018 kg |
| IP Code | IP 44 |
| Safety class | I |
| Impact resistance class | IK04 |
| Impact resistance | 0,5 Joule |
| Assembly | Surface |
| Assembly details | Ceiling,Ground,Wall |
| Wattage | 9.0 W |
| Color | grey |
| | |

| | | | | | | | 4 | | | | 4 | | | 4 | | ч | | ч | ч | ч | ч | ч | J | 4 | 4 | 4 | 4 | | | | | | | | |
|----|-----|-----|---|---|----|----|----|----|---|---|---|---|---|---|---|---|---|---|----|---|----|---|----|-----|---|---|----|----|---|----|----|----|---|---|---|
| | 4 | - 4 | | ı | a, | J, | J. | J | 4 | a | J | J | J | J | ä | ä | ä | ä | J. | | | | | | | | | | | | | | | | |
| ١. | ı . | LL | 1 | 1 | ı | ı | J | J. | 4 | 4 | J | J | J | J | J | J | J | | 1 | | | ı | | 1 | | 1 | ı | 1 | ı | J. | a, | ١, | 1 | 1 | 1 |
| | | | | | ı | | | á | | ä | | J | ä | J | ä | ä | J | J | J. | J | J. | 1 | J. | . د | 1 | J | J. | ă, | | | | | | | |



| Notes | | | |
|-------|--|--|--|
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |