



NEW TRIA 1 recessed fitting

single-headed, QR-C51, square, black, max. 50W, incl. leaf springs

The square, low-voltage version of our popular NEW TRIA recessed fitting series is available with black, white or brushed aluminium housings. The generous rotation and pivoting range of this recessed spot guarantees you the ability to individually focus its light beam, regardless of whether you choose to use halogen or LED retrofit lamps. Installation is carried out using the factory installed leaf springs. For operation of the NEW TRIA recessed fitting you only need a matching transformer with 12V alternating current.

TECHNICAL DATA

Item no.:	111700
Socket	GX5.3
Lamp	QR-C51
Number of sockets	1
Lamps included	0
Primary nominal voltage	12V ~50Hz mA/V
Tilt range	30 °
Horizontal rotation range	360 °
Length	9.0 cm
Width	9.0 cm
Height	11.0 cm
Installation diameter	7.8 cm
Installation depth	10.5 cm
Net weight	0.176 kg
Gross weight	0.205 kg
IP Code	IP 20
Safety class	III
Assembly	Recessed
Assembly details	Ceiling
Wattage	50.0 W
Color	black

Recommended lamp

1001574	Philips Master LED Spot MR16 , 5W, 2700K, 36°, dimmable
1001575	Philips Master LED MR16 5W , 3000K, 36°

Accessories

461157	ELECTRONIC TRANSFORMER 03 , 150VA, 12V
--------	--

Notes
