



INDI REC

recessed fitting, double-headed, QR-C51, rectangular, silver-grey, tiltable max. 70W

The double-headed low-voltage recessed fitting INDI REC is multi-directional and was conceived for use with low voltage halogen lamps. The steel housing has a silver-grey exterior and black interior. To operate the recessed fitting, a matching transformer with 12V alternating current is required.

TECHNICAL DATA

| | |
|-------------------------|-------------------|
| Item no.: | 112464 |
| Socket | GU5.3 |
| Lamp | QR-C51 |
| Number of sockets | 2 |
| Lamps included | 0 |
| Primary nominal voltage | 12V ~50/60Hz mA/V |
| Tilt range | 70 ° |
| Length | 18.0 cm |
| Width | 9.0 cm |
| Height | 14.0 cm |
| Installation length | 17.5 cm |
| Installation width | 7.0 cm |
| Net weight | 0.547 kg |
| Gross weight | 0.629 kg |
| IP Code | IP 20 |
| Safety class | III |
| Assembly | Recessed |
| Assembly details | Ceiling |
| Wattage | 35.0 W |
| Color | grey |

Accessories

| | |
|--------|--|
| 410140 | LOW-VOLTAGE DISTRIBUTION BOX , 6-way, max. 250W |
| 461060 | MINI TRANSFORMER 1 , 60VA, 12V, L/W/H 10.5/3.3/2.2 cm |

Notes
