


## H-LIGHT 1

recessed fitting, LED, 2700K, round, black, 20°, 11,5W, incl. driver, clip spring

The H-LIGHT 1 recessed fitting series impresses with its simple and elegant design, the integrated warm-white LED module with its narrow 20° beam angle ensures a discreet and ambience-oriented radiance. Thanks to the LED driver included in the set, the luminaire is immediately ready for connection to a 230V power supply.



## TECHNICAL DATA

|                                     |                        |
|-------------------------------------|------------------------|
| Item no.:                           | 114480                 |
| Primary nominal voltage             | 220-240V ~50/60Hz mA/V |
| Secondary power / secondary voltage | 500 mA/V               |
| Vertical tilting range              | 15 °                   |
| Height                              | 8.0 cm                 |
| Diameter                            | 9.0 cm                 |
| Installation diameter               | 8.0 cm                 |
| Installation depth                  | 8.0 cm                 |
| Net weight                          | 0.337 kg               |
| Gross weight                        | 0.416 kg               |
| IP Code                             | IP 20                  |
| Safety class                        | II                     |
| Assembly                            | Recessed               |
| Assembly details                    | Ceiling                |
| Wattage                             | 11.0 W                 |
| Lumen                               | 265 lm                 |
| Colour temperature                  | 2700 Kelvin            |
| Beam angle                          | 20 °                   |
| Color                               | black                  |
| CRI                                 | >80                    |
| Binning                             | 3                      |
| LXXBXX data                         | 70/50                  |



|                |         |
|----------------|---------|
| Service life   | 40000 h |
| BIG WHITE Page | 458     |

**Notes**

---

---

---

---

---