



CRYSTAL 1

recessed fitting, QR51, square, chrome/clear crystal, max. 35W

With the low-voltage recessed fitting series CRYSTAL we offer recessed fittings made from crystal glass, creating various prismatic effects of the halogen bulb in use. To operate the recessed fitting, a matching transformer with 12V alternating current is required.

TECHNICAL DATA

Item no.:	114920
Socket	GU5.3
Lamp	QR-C51
Number of sockets	1
Lamps included	0
Primary nominal voltage	12V ~50Hz mA/V
Length	10.2 cm
Width	10.2 cm
Height	2.7 cm
Installation diameter	6.4 cm
Installation depth	8.0 cm
Net weight	0.57 kg
Gross weight	0.614 kg
IP Code	IP 20
Safety class	III
Assembly	Recessed
Assembly details	Ceiling
Wattage	35.0 W
Color	chrome

Recommended lamp

1001574	Philips Master LED Spot MR16 , 5W, 2700K, 36°, dimmable
1001575	Philips Master LED MR16 5W , 3000K, 36°

Accessories

410140	LOW-VOLTAGE DISTRIBUTION BOX , 6-way, max. 250W
461060	MINI TRANSFORMER 1 , 60VA, 12V, L/W/H 10.5/3.3/2.2 cm

Notes
