





SUPROS

recessed fitting, LED, 3000K, round, tiltable, black, 3100lm, 60° reflector, 33.5W

The SUPROS light series impresses with its multitude of possible applications, excellent LED technology and its harmonious design. With its very high luminous flux, the SUPROS product family is ideally suited to replace power-hungry, conventional lighting installations. The wide-area reflector included in the delivers can be replaced by reflectors with narrower beam angles which are optionally available. This can be done without the need for tools. With the factory-installed LED driver, all the luminaires in the series are suitable for direct connection to the 230V mains supply.



TECHNICAL DATA

| | |
|-------------------------------------|------------------------|
| Item no.: | 118120 |
| Lamps included | 0 |
| Primary nominal voltage | 220-240V ~50/60Hz mA/V |
| Secondary power / secondary voltage | 950 mA/V |
| Vertical tilting range | 60 ° |
| Horizontal rotation range | 350 ° |
| Height | 17.0 cm |
| Diameter | 19.5 cm |
| Installation diameter | 18.0 cm |
| Installation depth | 11.5 cm |
| Net weight | 1.561 kg |
| Gross weight | 1.745 kg |
| IP Code | IP 20 |
| Safety class | II |
| Assembly | Recessed |
| Assembly details | Ceiling |
| Wattage | 36.0 W |
| Lumen | 3100 lm |
| Colour temperature | 3000 Kelvin |
| Beam angle | 60 ° |
| Color | black |
| CRI | >80 |

Accessories

| | |
|--------|--|
| 114102 | REFLECTOR , for SUPROS, 20°, incl. glass and fixing ring |
| 114104 | REFLECTOR , for SUPROS, 40°, incl. glass and fixing ring |

| | |
|----------------|---------|
| Binning | 3 |
| LXXBXX data | 70/50 |
| Service life | 50000 h |
| BIG WHITE Page | 507 |

Notes
