

CUBIX 2 outdoor floor stand

double-headed, QPAR51, IP44, silver-grey, energy saving lamp, max. 100W

The CUBIX 2 mobile aluminium luminaire is protection class IP44 and suitable for outdoor areas. The two lamp heads which are mounted on the frame are separately tiltable for optimum illumination. The electrical connection is made using the fitted cable and mains plug directly to the 230V supply.

TECHNICAL DATA

Socket GU10 Lamp QPAR51 Number of sockets 2 Lamps included 0 Primary nominal voltage 230V ~50Hz mA/V Tilt range 100 ° Width 18.0 cm Height 14.0 cm Depth 11.0 cm Net weight 1.093 kg Gross weight 1.235 kg IP Code IP 44 Safety class I Impact resistance class IK04 Impact resistance 0,5 Joule	Item no.:	132842		
Number of sockets 2 Lamps included 0 Primary nominal voltage 230V ~50Hz mAVV Tilt range 100 ° Width 18.0 cm Height 14.0 cm Depth 11.0 cm Net weight 1.093 kg Gross weight 1.235 kg IP Code IP 44 Safety class I Impact resistance class IK04 Impact resistance 0,5 Joule	Socket	GU10		
Lamps included 0 Primary nominal voltage 230V ~50Hz mA/V Tilt range 100 ° Width 18.0 cm Height 14.0 cm Depth 11.0 cm Net weight 1.093 kg Gross weight 1.235 kg IP Code IP 44 Safety class I Impact resistance class IK04 Impact resistance 0,5 Joule	Lamp	QPAR51		
Primary nominal voltage 230V ~50Hz mA/V Tilt range 100 ° Width 18.0 cm Height 14.0 cm Depth 11.0 cm Net weight 1.093 kg Gross weight 1.235 kg IP Code IP 44 Safety class I Impact resistance class IK04 Impact resistance 0,5 Joule	Number of sockets	2		
Tilt range 100 ° Width 18.0 cm Height 14.0 cm Depth 11.0 cm Net weight 1.093 kg Gross weight 1.235 kg IP Code IP 44 Safety class I Impact resistance class IK04 Impact resistance 0,5 Joule	Lamps included	0		
Width 18.0 cm Height 14.0 cm Depth 11.0 cm Net weight 1.093 kg Gross weight 1.235 kg IP Code IP 44 Safety class I Impact resistance class IK04 Impact resistance 0,5 Joule	Primary nominal voltage	230V ~50Hz mA/V		
Height	Tilt range	100 °		
Depth 11.0 cm Net weight 1.093 kg Gross weight 1.235 kg IP Code IP 44 Safety class I Impact resistance class IK04 Impact resistance 0,5 Joule	Width	18.0 cm		
Net weight 1.093 kg Gross weight 1.235 kg IP Code IP 44 Safety class I Impact resistance class IK04 Impact resistance 0,5 Joule	Height	14.0 cm		
Gross weight 1.235 kg IP Code IP 44 Safety class I Impact resistance class IK04 Impact resistance 0,5 Joule	Depth	11.0 cm		
IP Code IP 44 Safety class I Impact resistance class IK04 Impact resistance 0,5 Joule	Net weight	1.093 kg		
Safety class I Impact resistance class IK04 Impact resistance 0,5 Joule	Gross weight	1.235 kg		
Impact resistance class IK04 Impact resistance 0,5 Joule	IP Code	IP 44		
Impact resistance 0,5 Joule	Safety class	I		
·	Impact resistance class	IK04		
	Impact resistance	0,5 Joule		
Assembly Mobile	Assembly	Mobile		
Wattage 25.0 W	Wattage	25.0 W		
Color grey	Color	grey		





Recommended lamp

1004973	LED QPAR51 , lightbulb GU10 300K 36°
1005080	LED lightbulb QPAR51 , GU10, 3000K, black

Notes			