

BIMA 2

spot for 240V 1-phase track, double-headed, QPAR51, silver-grey, max. 50W, incl. 1-phase adapter

Double-headed adjustable high-voltage spot BIMA 2 with suitable adapter for the 240V 1-phase track system. The luminaire is made of aluminium and has a GU10 socket installed which makes it suitable for both halogen and LED lamps. Both lamp heads are separately adjustable.

TECHNICAL DATA

| Item no.: | 143432 | | |
|---------------------------|------------------------|--|--|
| Socket | GU10 | | |
| Lamp | QPAR51 | | |
| Number of sockets | 2 | | |
| Lamps included | 0 | | |
| Primary nominal voltage | 220-240V ~50/60Hz mA/V | | |
| Tilt range | 200° | | |
| Horizontal rotation range | 350 ° | | |
| Length | 8.0 cm | | |
| Height | 14.0 cm | | |
| Diameter | 6.0 cm | | |
| Net weight | 0.395 kg | | |
| Gross weight | 0.511 kg | | |
| IP Code | IP 20 | | |
| Safety class | II | | |
| Assembly | Surface | | |
| Assembly details | Ceiling,Track Ceiling | | |
| Wattage | 50.0 W | | |
| Color | grey | | |
| BIG WHITE Page | 391 | | |





Recommended lamp

| 1005080 | LED lightbulb QPAR51 , GU10, 3000K, black |
|---------|---|
| 1005083 | LED lightbulb QPAR51 , GU10, 4000K, black |

| Notes | | | |
|-------|--|--|--|
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |