




GILALED

recessed fitting, LED, 3000K, matt white, incl. position light, warm-white

Designed for space-saving recessed wall installation, the GILALED reading light provides an innovative and user-friendly lighting concept. The elegant luminaire is made from silver-grey or white coated aluminium and offers professionally manufactured mechanic, along with modern LED technology. If needed, the lamp can be folded out and instead of the white glowing orientation light a powerful and pure white 3W Power LED will appear. A suitable constant current driver providing 700mA is required to operate the recessed luminaire. We strongly recommend our model 464200. This luminaire contains built-in LED lamps.



TECHNICAL DATA

Item no.:	146362
Lamps included	0
Secondary power / secondary voltage	700 mA/V
Vertical tilting range	180 °
Horizontal rotation range	355 °
Height	6.3 cm
Diameter	11.2 cm
Installation diameter	10.2 cm
Net weight	0.418 kg
Gross weight	0.48 kg
IP Code	IP 20
Safety class	III
Assembly	Recessed
Assembly details	Wall
Wattage	3.0 W
Lumen	130 lm
Colour temperature	3000 Kelvin
Color	white
CRI	>90
LXXBXX data	70/50
Service life	30000 h

Accessories

464200	LED DRIVER , 3W, 700mA, incl. strain relief
--------	---

Notes
