



KALU

wall and ceiling light, single-headed, QR111, round, brushed aluminium, max. 50 W

The puristic design of the wall and ceiling light KALU is a guarantor for absolutely individual alignment of lamp heads, optionally equipped with QRB halogen or suitable LED lamps. Equipped with soft-start function, the incorporated electronic transformer protects the bulbs from potential damage from over-voltage. The light can be dimmed which offers even more installation possibilities. Available in matt white, matt black or brushed aluminium colour, KALU is supplied ready for direct connection to 230V mains supply.

TECHNICAL DATA

Item no.:	147256
Socket	G53
Lamp	QR111
Number of sockets	1
Lamps included	0
Primary nominal voltage	230V ~50Hz mA/V
Secondary power / secondary voltage	12 mA/V
Tilt range	90 °
Horizontal rotation range	350 °
Width	15.0 cm
Height	19.0 cm
Depth	9.0 cm
Net weight	0.538 kg
Gross weight	0.705 kg
IP Code	IP 20
Safety class	I
Assembly	Surface
Assembly details	Ceiling, Wall
Wattage	50.0 W
Color	aluminium

Recommended lamp

551412	LED QRB111 , lamp, CREE XB-D LED, grey, 19,5W, 140°, 2700K
560231	PHILIPS MASTER LED AR111 , CRI90, 15W, 24°, 2700K, dimmable
560233	PHILIPS MASTER LED AR111 , CRI90, 15W, 24°, 3000K, dimmable

Notes
