



KALU FLOOR 1 floor stand

single-headed, QR-LP111, round, brushed aluminium, max. 50 W

The puristic design of KALU FLOOR 1 is a guarantor for absolutely individual alignment of lamp heads, optionally equipped with QRB halogen or suitable LED lamps. Equipped with soft-start function, the incorporated electronic transformer protects the bulbs from potential damage from over-voltage. Available in brushed aluminium colour, KALU FLOOR 1 floor stand is supplied ready for direct connection to 230V mains supply.

TECHNICAL DATA

Item no.:	147286
Socket	G53
Lamp	QR111
Number of sockets	1
Lamps included	0
Primary nominal voltage	230V ~50Hz mA/V
Secondary power / secondary voltage	12 mA/V
Tilt range	90 °
Horizontal rotation range	350 °
Length	15.0 cm
Width	9.0 cm
Height	19.2 cm
Net weight	0.736 kg
Gross weight	0.911 kg
IP Code	IP 20
Safety class	I
Impact resistance class	IK03
Impact resistance	0,3499999999999998 Joule
Assembly	Mobile
Wattage	50.0 W
Color	aluminium

Recommended lamp

560231	PHILIPS MASTER LED AR111 , CRI90, 15W, 24°, 2700K, dimmable
560233	PHILIPS MASTER LED AR111 , CRI90, 15W, 24°, 3000K, dimmable

Notes
