



KALU

wall and ceiling light, single-headed, QPAR111, round, brushed aluminium, max. 75 W

The puristic design of KALU ceiling light is a guarantor for absolutely individual alignment of lamp heads, optionally equipped with halogen or suitable LED ES111 lamps. The light can also be dimmed which offers even more installation possibilities. Available in several colour versions KALU ceiling light is supplied ready for direct connection to 230V mains supply.

TECHNICAL DATA

| | |
|-----------------------------|------------------------|
| Item no.: | 147306 |
| Socket | GU10 |
| Lamp | QPAR111 |
| Number of sockets | 1 |
| Lamps included | 0 |
| Primary nominal voltage | 220-240V ~50/60Hz mA/V |
| Tilt range | 90 ° |
| Horizontal rotation range | 350 ° |
| Length | 15.0 cm |
| Width | 9.0 cm |
| Height | 18.0 cm |
| Net weight | 0.493 kg |
| Gross weight | 0.687 kg |
| IP Code | IP 20 |
| Safety class | I |
| Assembly | Surface |
| Assembly details | Ceiling, Wall |
| Wattage | 75.0 W |
| Color | aluminium |
| Maximum ambient temperature | 40 °C |
| BIG WHITE Page | 304 |

Recommended lamp

| | |
|---------|--|
| 1001920 | VALETO® LED lamp , GU10, 2700-6500K, 25°, 9W |
| 1003087 | LED lamp , QPAR111, GU10, 4000K, 1100lm, 30°, dimmable |
| 1003094 | LED lamp , QPAR111, GU10, 2700K, 40°, dimmable |
| 1003095 | LED lamp , QPAR111, GU10, 4000K, 55°, dimmable |

Notes
