

RETROSIX

wall and ceiling light, double-headed, QR-LP111, clear acrylic glass, max. 100 W

With our high-voltage wall and ceiling light RETROSIX we offer a nostalgic design which, by modern interpretation, provides illumination with a distinctive character. It is available with either clear or blackened glass cover. Prepared for the use of low-voltage QRB or appropriate LED retrofit lamps, RETROSIX is ready for direct connection to 230V mains supply via the incorporated, electronic transformer.

TECHNICAL DATA

Item no.:	147582
Socket	G53
Lamp	QR111
Number of sockets	2
Lamps included	0
Primary nominal voltage	230-240V ~50/60Hz mA/V
Secondary power / secondary voltage	12 mA/V
Tilt range	60 °
Horizontal rotation range	360 °
Length	40.0 cm
Width	17.5 cm
Height	12.8 cm
Net weight	2.04 kg
Gross weight	2.305 kg
IP Code	IP 20
Safety class	I
Assembly	Surface
Assembly details	Ceiling,Wall
Wattage	50.0 W
Color	aluminium

							4				4			4		ч		ч	ч	ч	ч	ч	J	4	4	4	4								
	4	- 4		ı	a,	J,	J.	J	4	a	J	J	J	J	ä	a	ä	ä	J.																
١.	ı .	LL	1	1	ı	ı	J	J.	J	4	J	J	J	J	J	J	J		1			ı		1		1	ı	1	ı	J.	a,	١,	1	1	1
					ı			á		ā		J	ä	J	ä	ä	J	J	J.	J	J.	J.	J.	. د	1	J	J.	ă,							



Notes			