


DOWNUNDER PUR 155

recessed fitting, LED, 3000K, square, white, L/W/H 12/3.2/15.5 cm, incl. leaf springs

Aluminium recessed wall light of our DOWNUNDER LED series. The not visibly mounted LED emits the light indirectly onto the surface to be illuminated. This guarantees glare-free illumination of walkways and much more. The DOWNUNDER PUR 120 recessed fitting is available in white colour version. To operate the recessed fitting, a suitable LED driver is required providing 480mA. A mounting frame for installation in masonry can be ordered from the accessory. This luminaire contains built-in LED lamps.

TECHNICAL DATA

Item no.:	151952
Lamps included	0
Secondary power / secondary voltage	500 mA/V
Width	12.0 cm
Height	15.5 cm
Depth	3.2 cm
Installation length	14.0 cm
Installation width	10.5 cm
Installation depth	3.5 cm
Net weight	0.242 kg
Gross weight	0.318 kg
IP Code	IP 20
Safety class	III
Assembly	Recessed
Assembly details	Wall
Wattage	5.2 W
Lumen	230 lm
Colour temperature	3000 Kelvin
Color	white
CRI	>80
LXXBXX data	70/50
Service life	30000 h



Accessories

151962	FLUSH-MOUNTED FRAME , for DOWNUNDER PUR 155, L/H 18/20.5 cm
464091	LED DRIVER , 9VA, 500mA, incl. strain relief
464144	LED DRIVER , 15W, 500mA, incl. strain relief, dimmable

Notes
