



DOWNUNDER 5

wall and ceiling light, QT12, square, natural aluminium, GY6,35, max. 50W

Aluminium recessed wall light of our DOWNUNDER 5 series. The not visibly mounted GY6.35 low-voltage halogen source emits the light indirectly onto the surface to be illuminated. This guarantees glare-free illumination of walkways and much more. The DOWNUNDER 5 recessed luminaire is available in natural aluminium colour version. To operate the recessed fitting, a matching transformer with 12V alternating current is required. A mounting frame for installation in masonry can be ordered from the accessory.

TECHNICAL DATA

Item no.:	151973
Socket	GY6.35
Lamp	QT12
Number of sockets	1
Lamps included	0
Primary nominal voltage	12V ~50Hz mA/V
Width	19.5 cm
Height	7.0 cm
Depth	7.0 cm
Net weight	0.453 kg
Gross weight	0.571 kg
IP Code	IP 20
Safety class	III
Assembly	Recessed
Assembly details	Ceiling
Wattage	50.0 W
Color	aluminium

Accessories

461060	MINI TRANSFORMER 1 , 60VA, 12V, L/W/H 10.5/3.3/2.2 cm
925195	FLUSH-MOUNTED FRAME , for DOWNUNDER 05

Notes
