

BIMA 1

spot for 240V 3-phase track, single-headed, QPAR51,round, matt white, max. 50W, incl. 3-phase adapter

Adjustable high-voltage spot BIMA 1 with suitable adapter for the 240V 3-phase track system. The luminaire is made of aluminium and, thanks to the GU10 socket, is suitable for both halogen and LED lamps.

TECHNICAL DATA

| Item no.: | 152241 | | |
|---------------------------|------------------------|--|--|
| Socket | GU10 | | |
| Lamp | QPAR51 | | |
| Number of sockets | 1 | | |
| Lamps included | 0 | | |
| Primary nominal voltage | 220-240V ~50/60Hz mA/V | | |
| Tilt range | 200° | | |
| Horizontal rotation range | 350 ° | | |
| Length | 8.0 cm | | |
| Height | 15.0 cm | | |
| Diameter | 6.0 cm | | |
| Net weight | 0.293 kg | | |
| Gross weight | 0.296 kg | | |
| IP Code | IP 20 | | |
| Safety class | Ш | | |
| Assembly | Surface | | |
| Assembly details | Ceiling, Track Ceiling | | |
| Wattage | 50.0 W | | |
| Color | white | | |
| BIG WHITE Page | 351 | | |





Recommended lamp

| 1001030 | LED QPAR51 GU10 , lamp, 38°, 2700K, 400 lm, dimmable | | |
|---------|--|--|--|
| 1005079 | LED lightbulb QPAR51 , GU10, 3000K, white | | |

| Notes | | | |
|-------|--|--|--|
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |