

DOWNLIGHT 20

recessed fitting, LED, 4000K, round, white, 15W

The DOWNLIGHT 20 is fitted with an integrated 15W SMD LED. The recessed fitting is made from aluminium and plastic and is available with either a neutral or warm-white coloured light, as well as with a white coloured housing. Thanks to the built-in LED driver, the DOWNLIGHT 20 is ready for direct connection to the 230V mains supply.

TECHNICAL DATA

Item no.:	160451
Lamps included	0
Primary nominal voltage	100-240V ~50/60Hz mA/V
Secondary power / secondary voltage	290 mA/V
Height	12.3 cm
Diameter	19.7 cm
Installation diameter	18.5 cm
Installation depth	13.0 cm
Net weight	0.479 kg
Gross weight	0.713 kg
IP Code	IP 20
Safety class	II
Assembly	Recessed
Assembly details	Ceiling
Wattage	16.0 W
Lumen	1250 lm
Colour temperature	4000 Kelvin
Beam angle	100 °
Color	white
CRI	>80
LXXBXX data	70/50
Service life	20000 h

							4				4			4		ч		ч	ч	ч	ч	ч	J	4	4	4	4								
	4	- 4		ı	a,	J,	J.	J	4	a	J	J	J	J	ä	a	ä	ä	J.																
١.	ı .	LL	1	1	ı	ı	J	J.	J	4	J	J	J	J	J	J	J		1			ı		1		1	ı	1	ı	J.	a,	١,	L	1	1
					ı			á		ā		J	ä	J	ä	ä	J	J	J.	J	J.	J.	J.	. د	1	J	J.	ă,							



Notes			