



KANO

spot for 240V track EASYTEC II, QPAR51, silver-grey, max. 50W

The high-voltage spot KANO with incorporated adapter for the EASYTEC II rail system can be rotated and swivelled. Made from aluminium with frosted glass parts, KANO is suitable for the use of either halogen or LED lamps thanks to the incorporated GU10 high-voltage socket.

TECHNICAL DATA

| | |
|---------------------------|------------------------|
| Item no.: | 184071 |
| Socket | GU10 |
| Lamp | QPAR51 |
| Number of sockets | 1 |
| Lamps included | 0 |
| Primary nominal voltage | 220-240V ~50/60Hz mA/V |
| Tilt range | 90 ° |
| Horizontal rotation range | 350 ° |
| Length | 18.0 cm |
| Height | 11.0 cm |
| Diameter | 6.5 cm |
| Net weight | 0.38 kg |
| Gross weight | 0.467 kg |
| IP Code | IP 20 |
| Safety class | I |
| Assembly | Surface |
| Assembly details | Ceiling, Track Ceiling |
| Wattage | 50.0 W |
| Color | grey |
| BIG WHITE Page | 412 |

Recommended lamp

| | |
|---------|--|
| 1001030 | LED QPAR51 GU10 , lamp, 38°, 2700K, 400 lm, dimmable |
| 1005079 | LED lightbulb QPAR51 , GU10, 3000K, white |

Notes
