


VANO WING

outdoor floodlight, LED, 3000K, silver-grey, W/H/D
119.5/6.5/20.5 cm

Single-headed luminaire of the VANO series made from aluminium for area or display and advertising board illumination. The dimmable VANO WING LED is suitable for wall, ground and ceiling mounting. Thanks to the integrated asymmetrical reflector, an even and wide-area lighting is possible even at small separation distances to the illuminated surface. Thanks to the built-in LED driver, the luminaire can be connected directly to the 230V mains supply. With protection class IP65 it is suitable for outdoor use. The assembly holders make assembly easier.

TECHNICAL DATA

Item no.:	227744
Lamps included	0
Number of different light outlets	1
Primary nominal voltage	120-277V ~50/60Hz mA/V
Secondary power / secondary voltage	1050 mA/V
Vertical tilting range	180 °
Width	119.5 cm
Height	6.5 cm
Depth	20.5 cm
Net weight	6.01 kg
Gross weight	6.923 kg
IP Code	IP 65
Safety class	I
Impact resistance class	IK02
Impact resistance	0,200000000000000001 Joule
Assembly	Surface
Assembly details	Ceiling,Ground,Wall
Wattage	48.0 W
Lumen	3340 lm
Colour temperature	3000 Kelvin
Beam angle	120 °
Color	grey





CRI	>80
Binning	6
LXXBXX data	70/50
Service life	25000 h
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
BIG WHITE Page	608

Notes
