


FRAME OUTDOOR

recessed wall light, LED, 3000K, IP44, square, stainless steel, 1.5W

With the weather-resistant and stainless steel-made recessed wall light FRAME OUTDOOR, the installed SMD LEDs are covered by a frosted glass pane. With protection class IP44, the luminaire is available in several colours of light and is suitable for outdoor use. The electrical connection is made directly to the 230V mains supply thanks to the built-in power supply. A mounting pot is included in the delivery for simple assembly.



TECHNICAL DATA

| Item no.: | 230132 |
|-------------------------|-----------------|
| Lamps included | 0 |
| Primary nominal voltage | 230V ~50Hz mA/V |
| Width | 10.5 cm |
| Height | 10.5 cm |
| Depth | 8.2 cm |
| Installation length | 6.9 cm |
| Installation width | 6.9 cm |
| Installation depth | 8.9 cm |
| Net weight | 0.492 kg |
| Gross weight | 0.553 kg |
| IP Code | IP 44 |
| Safety class | I |
| Assembly | Recessed |
| Assembly details | Wall |
| Wattage | 1.5 W |
| Lumen | 40 lm |
| Colour temperature | 3000 Kelvin |
| Color | stainless steel |
| CRI | >80 |
| LXXBXX data | 70/50 |
| Service life | 20000 h |
| | |

| | | | | | | | 4 | | | | 4 | | | 4 | | ч | | ч | ч | ч | ч | ч | J | 4 | 4 | 4 | 4 | | | | | | | | |
|----|-----|-----|---|---|----|----|----|----|---|---|---|---|---|---|---|---|---|---|----|---|----|---|----|-----|---|---|----|----|---|----|----|----|---|---|---|
| | 4 | - 4 | | ı | a, | J, | J. | J | 4 | a | J | J | J | J | ä | ä | ä | ä | J. | | | | | | | | | | | | | | | | |
| ١. | ı . | LL | 1 | 1 | ı | ı | J | J. | 4 | 4 | J | J | J | J | J | J | J | | 1 | | | ı | | 1 | | 1 | ı | 1 | ı | J. | a, | ١, | 1 | 1 | 1 |
| | | | | | ı | | | á | | ä | | J | ä | J | ä | ä | J | J | J. | J | J. | 1 | J. | . د | 1 | J | J. | ă, | | | | | | | |



| Notes | | | |
|-------|--|--|--|
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |