



N-TIC

outdoor inground fitting, QR-C51, IP67, round, brushed stainless steel 316, max. 35W

The walkable low-voltage inground fitting with round stainless steel shade and partially frosted glass cover is equipped with a G5.3 socket and is thus compatible with halogen and LED lamps. With its IP67 protection class, the luminaire is suitable for outdoor use. The electrical connection is made to a 12V low-voltage transformer available separately. A mounting pot is included for simplified installation. Alternatively to the floor, the luminaire can also be mounted flush with the wall.

TECHNICAL DATA

Item no.:	230900
Socket	GU5.3
Lamp	QR-C51
Number of sockets	1
Lamps included	0
Primary nominal voltage	12V ~50/60Hz mA/V
Tilt range	30 °
Horizontal rotation range	90 °
Diameter	13.5 cm
Depth	11.5 cm
Installation diameter	12.3 cm
Net weight	1.795 kg
Gross weight	1.903 kg
IP Code	IP 67
Safety class	III
Impact resistance class	IK08
Impact resistance	5 Joule
Assembly	Recessed
Assembly details	Ground
Wattage	35.0 W
Color	stainless steel
Mechanical loading	5 t

Recommended lamp

1001574	Philips Master LED Spot MR16 , 5W, 2700K, 36°, dimmable
1001575	Philips Master LED MR16 5W , 3000K, 36°

Accessories

227160	TRANSFORMER , 60VA, 12V, IP44
--------	-------------------------------

Notes
