




## MERVALED

outdoor wall light, LED, 3000K, IP54, anthracite, 14W

Powerful LED outdoor spot MERVALED for illuminating areas and spaces. By means of the adjustable lamp head and its IP54 protection, the spot is suitable for exterior wall mounting. The electrical connection of the luminaire, which is available in warm white light colour, is made directly to the 230V mains supply thanks to the built-in LED driver.



## TECHNICAL DATA

|                                     |                        |
|-------------------------------------|------------------------|
| Item no.:                           | 232415                 |
| Lamps included                      | 0                      |
| Primary nominal voltage             | 220-240V ~50/60Hz mA/V |
| Secondary power / secondary voltage | 300 mA/V               |
| Vertical tilting range              | 180 °                  |
| Horizontal rotation range           | 340 °                  |
| Width                               | 14.0 cm                |
| Height                              | 26.5 cm                |
| Depth                               | 22.5 cm                |
| Net weight                          | 1.213 kg               |
| Gross weight                        | 1.415 kg               |
| IP Code                             | IP 54                  |
| Safety class                        | I                      |
| Assembly                            | Surface                |
| Assembly details                    | Wall                   |
| Wattage                             | 14.0 W                 |
| Lumen                               | 1000 lm                |
| Colour temperature                  | 3000 Kelvin            |
| Beam angle                          | 30 °                   |
| Color                               | anthracite             |
| CRI                                 | >80                    |
| Binning                             | 6                      |



|                |         |
|----------------|---------|
| LXXBXX data    | 70/50   |
| Service life   | 30000 h |
| BIG WHITE Page | 637     |

**Notes**

---

---

---

---

---