



## P-LIGHT 27

wall and ceiling light, emergency exit light, LED, 6000K, white, L/W/H 26.5/4.5/21 cm, 3,5W

The P-LIGHT 27 emergency lighting system is suitable for use as a wall and ceiling light. The safety lights are fitted with a built-in Ni-MH battery with an automatic self-test. The detection range is 24 m. The emergency operating time of the luminaires is three hours. The luminaires can be operated permanently switched on / stand-by operation. The luminaire is connected directly to the 230V mains supply. Other variants of the P-LIGHT series are available. The luminaire is supplied with three signs with different arrow directions (right / left / down). As an option, other signs are available.

## TECHNICAL DATA

Item no.:	240000
Lamps included	0
Number of different light outlets	1
Primary nominal voltage	220-240V ~50Hz mA/V
Width	26.5 cm
Height	21.0 cm
Depth	4.5 cm
Net weight	0.84 kg
Gross weight	0.99 kg
IP Code	IP 20
Safety class	II
Assembly	Surface
Assembly details	Ceiling, Wall
Wattage	3.5 W
Lumen	32 lm
Colour temperature	6000 Kelvin
Color	white
CRI	>70
LXXBXX data	70/50
Service life	25000 h
BIG WHITE Page	740

## Accessories

240007	PICTOGRAM FOILS , for P-LIGHT emergency exit light, set of 4, diagonal arrow in all directions, L/H 24/13.1 cm
240020	RECHARGEABLE BATTERY , for P-LIGHT, 3.6V, 900mA

## Notes

---

---

---

---

---