

## **FLEXLED ROLL**

12V, 12W, 2700K, 3 m, 60 LED/m

Flexible 12V DC LED strip. For simplified mounting the backside is covered with adhesive tape. The power input is given by a 12V direct current power supply unit. We further offer accessory like feed cables, direct connectors and 90° soldering edges.

## **TECHNICAL DATA**

Item no.:	552010
Nominal voltage	12V DC V
Length	300.0 cm
Width	0.8 cm
Height	0.2 cm
Net weight	0.038 kg
Gross weight	0.148 kg
IP Code	IP 20
Safety class	III
Wattage	12.0 W
Lumen	1050 lm
Colour temperature	3000 Kelvin
Beam angle	120 °
CRI	>80
Binning	6
Service life	20000 h
Switching cycles	10000

							ч				4			ч		4		ч	ч	ч	ч	4	7	ч	ч	ч	4									
	- 4	- 4		a,	a,	J	J.	J	J	J	J	J	J	J	ä	ä	ä	ä	J.																	
ı	J J .	ר ר	ı	J	ı	J	J	J.	J	ä	J	J	J	J	J	J	J		1			ı		1		1	4	1	ı	ı	a,	J.	ı	ı	1	١,
					ă,			á		ä		J	ä	J	ä	J	J	J	J.	J	ă,	a.	J.	J	J	J	J.	ă,								


