

FLEXLED ROLL

12V, 20W, 2700K, 5m, 60 LED/m

Flexible 12V DC LED strip. For simplified mounting the backside is covered with adhesive tape. The power input is given by a 12V direct current power supply unit. We further offer accessory like feed cables, direct connectors and 90° soldering edges.

TECHNICAL DATA

Item no.:	552020
Nominal voltage	12V DC V
Length	500.0 cm
Width	0.8 cm
Height	0.2 cm
Net weight	0.059 kg
Gross weight	0.17 kg
IP Code	IP 20
Safety class	III
Wattage	20.0 W
Lumen	1750 lm
Colour temperature	3000 Kelvin
Beam angle	120°
CRI	>80
Binning	6
Service life	20000 h
Switching cycles	10000

							4				4			4		ч		ч	ч	ч	ч	ч	J	4	4	4	4								
	4	- 4		ı	a,	J,	J.	J	4	a	J	J	J	J	ä	ä	ä	ä	J.																
١.	ı .	LL	1	1	ı	ı	J	J.	4	4	J	J	J	J	J	J	J		4			ı		1		1	ı	1	ı	J.	a,	١,	L	1	1
					ı			á		ä		J	ä	J	ä	ä	J	J	J.	J	J.	1	J.	. د	1	J	J.	ă,							



Notes			