

FLEXLED ROLL PRO

12V, 30W, 3000K, 3 m, 60 LED/m

High-performance flexible 12V DC LED strip of the PRO series . For simplified mounting the backside is covered with adhesive tape. The power input is given by a 12V PSU. This strip is available in several lengths and colours. Further available are connection leads, direct connectors and 90° soldering edges.

TECHNICAL DATA

| Item no.: | 552072 |
|--------------------|-------------|
| Nominal voltage | 12V DC V |
| Length | 300.0 cm |
| Width | 1.0 cm |
| Height | 0.2 cm |
| Net weight | 0.056 kg |
| Gross weight | 0.165 kg |
| IP Code | IP 20 |
| Safety class | III |
| Assembly | Surface |
| Wattage | 30.0 W |
| Lumen | 2700 lm |
| Colour temperature | 3000 Kelvin |
| Beam angle | 120° |
| CRI | >80 |
| Binning | 6 |
| Service life | 20000 h |
| Switching cycles | 10000 |
| | |

| | | | | | | | 4 | | | | 4 | | | 4 | | ч | | ч | ч | ч | ч | ч | J | 4 | 4 | 4 | 4 | | | | | | | | |
|----|-----|-----|---|---|----|----|----|----|---|---|---|---|---|---|---|---|---|---|----|---|----|---|----|-----|---|---|----|----|---|----|----|----|---|---|---|
| | 4 | - 4 | | ı | a, | J, | J. | J | 4 | a | J | J | J | J | ä | ä | ä | ä | J. | | | | | | | | | | | | | | | | |
| ١. | ı . | LL | 1 | 1 | ı | ı | J | J. | 4 | 4 | J | J | J | J | J | J | J | | 1 | | | ı | | 1 | | 1 | ı | 1 | ı | J. | a, | ١, | 1 | 1 | 1 |
| | | | | | ı | | | á | | ā | | J | ä | J | ä | ä | J | J | J. | J | J. | 1 | J. | . د | 1 | J | J. | ă, | | | | | | | |



| Notes | | | |
|-------|--|--|--|
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |